


# Any Foam

## INDIVIDUAL SPECIFICATION SHEET

<b>Pink Anti Static Foam</b>	
<b><u>GRADE/REF : AS22</u></b>	
<b><u>CHARACTERISTIC</u></b>	<b><u>SPECIFICATION</u></b>
APPARENT PIECE DENSITY	20-23 Kg/m <sup>3</sup>
NOMINAL HARDNESS	100-150 Newtons
TENSILE STRENGTH	70 Kpa (Min)
ELONGATION @ BREAK	Min 150%
COMPRESSION@ SET	Max 10%
SURFACE RESISTIVITY	MAX 1X10(11) OHMS/SQ
SPECIFICATION	POLYURETHANE FOAM WITH INHERENT STATIC CONTROL PROPERTIES. SUITABLE FOR ELECTRONICS PACKAGING.

*Physical properties are measured using test methods described in BS EN ISO 845:1995. (Determination of Density), BS EN ISO 2439 (Determination of Hardness) and BS EN ISO1798 (Determination of Tensile Strength and Elongation).*



# Any Foam

All prices include VAT  
Next Day UK Delivery

Call us on Freephone  
**0800 193 4488**

Anyfoam Ltd, 2 Falcon Way, Shire Park, Welwyn Garden City, Hertfordshire, AL7 1TW  
[www.anyfoam.co.uk](http://www.anyfoam.co.uk)